

MLCC 107

LED Driver-Constant Current



Areas of application

- Suitable for indoor installations
- Suitable for luminaires of protection classes I and II

Product benefits

- Wide Operating Range 100...264 VAc
- O/P overload-S/C, over temperature Auto restart recovery protections,
- High efficiency and reliability,
- High quality of light.
- Small PCFR-White housing.
- Efficiency >85%.

Product features


- Supply voltage: 220...240 VAc
- Line frequency: 50 Hz | 60 Hz
- Line voltage: 100...264 VAc
- Safety according to EN 61347-1, 61347-2-13, 62384
- EMI CE suppression: to EN 55015A
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Lifetime: up to 50,000 h (temperature at $T_c = 65^\circ\text{C}$, max. 10 % failure rate)

Technical data

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	100-277VAc
Total harmonic distortion	NA
Power factor è	NA
ECG efficiency	>82%
Device power loss	<4.0 W
Inrush current	COLD START 20A(twidth=260 us measured at 50% Ipeak) at 230VAc
Surge capability (L/N-Ground)	1KV
Surge capability (L-N)	1.5KV
Nominal output voltage	3-12VDc
U-OUT (working voltage)	<60VDc
Nominal output current	700mA
Output current tolerance	±5 %
Output ripple (@100 Hz)	< 2 %
Nominal output power	4.5 W
Galvanic isolation	SELV

Dimensions & weight



Length	55mm
Width	21mm
Height	22mm
Mounting hole spacing, length	48mm

Product datasheet

Mounting hole spacing, width	34.0 mm
Product weight	145.00 gm
Cable cross-section, input side	0.5...1.5 mm ²
Cable cross-section, output side	0.5...1.5 mm ²
Wire preparation length, input side	6.5...7.5 mm
Wire preparation length, output side	6.5...7.5 mm

Colors & materials

Casing material	PC FR 94V0 White
-----------------	------------------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

Lifespan

ECG lifetime	min 30,000 h*
--------------	---------------

* At T_{case} = 65°C at T_c point / 10% failure rate

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	No
Overheating protection	Auto-recovery
Overload protection	Auto-recovery
Short-circuit protection	Auto-recovery
No-load proof	Yes
Max. cable length to lamp/LED module	1 meter
Suitable for fixtures with prot. class	Class I
Type of connection, output side	Screw terminal

Certificates & standards

Approval marks – approval	CE
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61547/Acc. to IEC 61000-3-3
Type of protection	IP20

Product datasheet

Logistical data

Temperature range at storage	-40...85 °C
------------------------------	-------------

Download Data

File
 Product Data sheet.pdf
 Brochure CC Drivers
 ROHs & WEEE Decl.pdf
 EMI-CE report.pdf
 EFT Test Report.pdf
 CAD data.zip

Logistical Data

Product code	Product description	Packaging unit (Pieces/Box)	Dimensions (length x width x Volume height)	Gross weight
MLCC107	O/P current fix	Per tray 50pc		1.6Kg
MLCC107	O/P current fix	Shipping carton box 100/Box (5 Trays/Box)		8Kg

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Ordering Information:

M

L

C

C

1

0

7

MELCON

LED

C-Constant
F-Flicker Free
D- Dimming
M- Master
S- Slave
N- Non-Isolated

A- Analog Dim
B-Bluetooth
C-Current
D-Dali Dim
P-PWM Dim
R-Potentiometer
S-Switch(AOI)
T-Triac Dim
V-Voltage
W-Wi-Fi
Z-Zigbee

O/P Voltage

O/P Power

Version Change History:

Sr.	Revision	Notes	Date