

MF8P236

Linear Electronic Ballast

Areas of application

- Suitable for indoor installations
- Suitable for luminaires of protection classes I and II



Product benefits

- Wide Operating Range 140~264VAc
- O/P overload-S/C, over temperature
- High efficiency and reliability,
- High quality of light.
- Small PCFR-White housing.
- ATHD<30 %,Efficiency >85%.

covery protections,

Product features

- Supply voltage: 220...240 VAc
- Line frequency: 50 Hz | 60 Hz
- Line voltage: 140...264 VAc
- Safety according to EN 61347-1, 61347-2-13, 62384
- EMI CE suppression: to EN 55015A
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Lifetime: up to 50,000 h (temperature at $T_c = 65^\circ\text{C}$, max. 10 % failure rate)

Product datasheet

Technical data

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	100...264 Vac
Total harmonic distortion	<30%
Power factor è	>0.96
ECG efficiency	>86%
Device power loss	<4.0 W
Inrush current	COLD START 20A(twidth=260 us measured at 50% Ipeak) at 230VAc
Surge capability (L/N-Ground)	2.5 kV

Dimensions & weight



Length	200mm
Width	40mm
Height	28mm
Mounting hole spacing, length	190mm

Product datasheet

Mounting hole spacing, width	4.0 mm
Product weight	145.00 gm
Cable cross-section, input side	0.5...1.5 mm ²
Cable cross-section, output side	0.5...1.5 mm ²
Wire preparation length, input side	6.5...7.5 mm
Wire preparation length, output side	6.5...7.5 mm

Colors & materials

Casing material	PC FR 94V0 White
-----------------	------------------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

Lifespan

ECG lifetime	min 30,000 h*
--------------	---------------

* At T_{case} = 65°C at T_c point / 10% failure rate

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	No
Overheating protection	Auto-recovery
No Lamp protection	Auto-recovery
Short-circuit protection	Auto-recovery
Input Fuse Protected	Yes
Max. cable length to lamp	1 meter
Suitable for fixtures with prot. class	Class II
Type of connection, output side	Screw terminal

Certificates & standards







Approval marks – approval	CE
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61547/Acc. to IEC 61000-3-3
Type of protection	IP20

Product datasheet

Logistical data

Temperature range at storage	-40...85 °C
------------------------------	-------------

Download Data

File	
	Product Data sheet.pdf
	Brochure
	ROHs & WEEE Decl.pdf
	EMI-CE report.pdf
	EFT Test Report.pdf
	CAD data.zip

Logistical Data

Product code	Product description	Packaging unit (Pieces/Box)	Dimensions (length x width x Volume height)		Gross weight
MF8P236	Electronic Ballast 2 x 36W	Per tray 20pc	240 mm x 210 mm x 80 mm		3.16 kg
MF8P236	Electronic Ballast 2 x 36W	Shipping carton box100/Box (5 Trays/Box)	240 mm x 210 mm x 80 mm	3.70 dm³	19.00 Kg

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Ordering Information:

M

F

8

P

2

3

6

MELCON

F-FTL
C-CFL
H-HALOGEN

8-T8
5-T5

A-ACTIVE PFC
P-PASSIVE PFC

LAMP/S

O/P LAMP

Version Change History:

Sr.	Revision	Notes	Date